

# RTV

# RTV900

# SPECIFICATIONS

## Specifications

Model		RTV900 General Purpose		RTV900 Worksite		RTV900 Utility
		Orange		Orange	Camouflage	Orange
Engine	Make	KUBOTA D902-E3-UV				
	Type	3-cylinders, 4-cycle, diesel, OHV				
	Displacement	cu.in (cc)	54.8 (898)			
	Horsepower	HP (kW)/rpm	21.6 (16.1)@3200			
Fuel tank capacity	U.S.gals (ℓ)	7.4 (28)				
Transmission	Variable hydro transmission (VHT Plus)					
Max. Traveling speed	mph (km/h)	25 (40)				
Wheels, drive system	4, Rear 2WD or 4WD					
Differential lock	Standard; foot operated with mechanical holder					
Gear selection	Hi-Med-Lo range forward, neutral, reverse					
Brakes	Front / Rear	Wet-disc brakes				
	Parking brake	Rear wheel, hand lever				
Steering	Hydrostatic power					
Suspension	Front / Rear	Independent, Mac-Pherson strut-type / Semi-independent, DeDion axle w/leaf springs and shock absorbers				
Dimensions	Length	in. (mm)	117.7 (2990)	119.3 (3030)		
	Width	in. (mm)	59.8 (1520)			
	Height, overall	in. (mm)	79.3 (2015)		79.1 (2010) [79.3(2015) with Turf Tires]	
	Front tread centers	in. (mm)	45.3(1150) w/HDWS & ATV, 46.5 (1180) w/Turf			
	Rear tread centers	in. (mm)	46.5(1180) w/HDWS & ATV, 47.6 (1210) w/Turf			
	Wheelbase	in. (mm)	77.4 (1965)			
	Ground clearance front/rear axle	in. (mm)	8.3 (210) / 7.5 (190)			
	Turning diameter	ft. (m)	25.6 (7.8)			
Max. rolling weight (Towing capacity)	lbs. (kg)	1300 (590)				
Payload capacity	lbs. (kg)	1653 (750)		1576 (715)		
Weight	lbs. (kg)	1863 (845)	1918 (870)	1907 (865)	1984 (900) [1995(905) with Turf Tires]	
Cargo bed	Width × Length × Depth	in. (mm)	52 (1320) × 46.7 (1180) × 11.4 (290)			
	Volume	cu ft. (m³)	16 (0.455)			
	Bed height (unloaded)	in. (mm)	31.5 (800)			
	Cargo bed load	lbs. (kg)	1102 (500)			
Sound level, operator ear	db. (A)	87 @ Max. engine speed w / no load				89 @ Max. engine speed w / no load
Tires	Front	25×10-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	25×10-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	
		25×10-12 HDWS, 6PLY	25×10-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	25×12-12 Turf, 4PLY	
		25×12-12 Turf, 4PLY	—	—	—	
	Rear	25×11-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	25×11-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	
		25×12-12 HDWS, 6PLY	25×11-12 ATV, 6PLY	25×10-12 HDWS, 6PLY	25×12-12 Turf, 4PLY	
		25×12-12 Turf, 4PLY	—	—	—	
Front guard	—	Std.	Std.	Std.		
Hydraulic bed lift	—	Std.	Std.	Std.		
Hydraulic Utility Valve	—	—	—	Std.		
Speedometer	—	—	—	Std.	Std.	

The company reserves the right to change the above specifications without notice. This brochure is for descriptive purposes only. Please contact your local Kubota dealer for warranty and safety information. The values in "Ground clearance" and "Weight" are those of the machine equipped with the tires in the table above. Some RTVs in this brochure are shown with optional accessories. For off-highway use only.